



Coupling Size	Type	Coupling Half									Insert Part Nos.					
		Min Bore	Max Bore	Setscrews	A	B	C	D	E	Weight kg	Buna-N	Urethane	Hydrel	Weight kg	Bronze	Weight kg
L035	1	-	9.5	-	15.9	20.6	7.2	6.7	-	.010	L035N	N/A	N/A	.002	N/A	-
L050	1	6	15.0	M5	27.4	43.7	11.9	15.9	-	.065	L050N	N/A	L050H	.007	L050B	.022
L070	1	9	19.0	M6	34.5	50.8	12.7	19.1	-	.135	L070N	L070U	L070H	.008	L070B	.028
L075	1	9	22.2	M6	44.5	54.0	12.7	20.6	-	.23	L075N	L075U	L075H	.012	L075B	.065
L090	1	9	25.4	M6	53.6	54.0	12.7	20.6	-	.36	L090N	L090U	L090H	.015	L090B	.100
L095	1	9	28.6	2xM6	53.6	63.5	12.7	25.4	-	.40	L090N	L090U	L090H	.015	L090B	.100
L099	1	12	30.2	2xM8	64.3	73.0	19.1	27.0	-	.61	L099N	L099U	L099H	.033	L099B	.150
L100	1	12	35.0	2xM8	64.3	89.0	19.1	34.9	-	.81	L099N	L099U	L099H	.033	L099B	.150
L110	1	15	41.3	2xM10	84.2	108.0	22.2	42.9	-	1.71	L110N	L110U	L110H	.065	L110B	.30
L150	1	15	47.6	2xM10	95.0	114.5	25.4	44.5	-	2.28	L150N	L150U	L150H	.095	L150B	.63
L190	2	20	54.0	2xM12	102.0	133.5	25.4	54.0	114.5	3.72	L190N	L190U	L190H	.145	L190B	.90
L225	2	20	60.0	2xM12	108.0	152.0	25.4	63.5	127.0	5.20	L225N	L225U	L225H	.190	L225B	1.12